

# APR Control Spec & Dimension Sheet

## R-410A

Model #	Modulation Capacity	Unit Dimensions			Connection Dimensions (OD)				G Location
		X	Y	Z	EE	L	M	G	
APR-410-1	1.5 tons	8.5"	8"	4"	N/A	3/8"	5/8"	3/8"	G – Bottom Connection
APR-410-2	2.5 tons	8.5"	8"	4"	1/4"	3/8"	5/8"	3/8"	G – Bottom Connection
APR-410-2R	3 tons	7.5"	8"	4"	1/4"	3/8"	5/8"	5/8"	G – Side Connection
APR-410-3	3.5 tons	8.5"	8"	4"	1/4"	3/8"	5/8"	3/8"	G – Bottom Connection
APR-410-5	5.5 tons	10"	10"	5"	1/4"	3/8"	5/8"	5/8"	G – Side Connection
APR-410-6	6.5 tons	9.5"	10"	4.5"	1/4"	3/8"	5/8"	5/8"	G – Side Connection
APR-410-10	10 tons	12"	11"	5.5"	1/4"	3/8"	7/8"	7/8"	G – Side Connection

## R-454B

Model #	Modulation Capacity	Unit Dimensions			Connection Dimensions (OD)				G Location
		X	Y	Z	EE	L	M	G	
APR-454-1	1.6 tons	8.5"	8"	4"	N/A	3/8"	5/8"	3/8"	G – Bottom Connection
APR-454-2	2.6 tons	8.5"	8"	4"	1/4"	3/8"	5/8"	3/8"	G – Bottom Connection
APR-454-2R	3 tons	7.5"	8"	4"	1/4"	3/8"	5/8"	5/8"	G – Side Connection
APR-454-3	3.6 tons	8.5"	8"	4"	1/4"	3/8"	5/8"	3/8"	G – Bottom Connection
APR-454-5	5.6 tons	10"	10"	5"	1/4"	3/8"	5/8"	5/8"	G – Side Connection
APR-454-6	6.7 tons	9.5"	10"	4.5"	1/4"	3/8"	5/8"	5/8"	G – Side Connection
APR-454-10	10 tons	12"	11"	5.5"	1/4"	3/8"	7/8"	7/8"	G – Side Connection

Please refer to Rawal Devices Engineering & Sales Team for proper APR Control Selection

Isolation Ball Valves/ Manual Shut-off Valves Required for ALL CONNECTIONS



Call Tech Support: (800) 727 – 6447

Email: [sales@rawal.com](mailto:sales@rawal.com)

Visit: [www.rawal.com](http://www.rawal.com)

